
ELRS-6WW7-K





quantity lamps: 1
Light up with: CoB-LED
System power: 6 W
Luminous flux: 537 lm
colour temperature: 3000 K
colour rendering index: CRI >80
pivotable: 30 °
Power supply: with power supply
connection voltage: 220-240 V
system efficiency: 89 lm/W
protection class: 2
outside diameter: 82 mm
wall and ceiling cut: 68 mm
weight: 0,274 kg
colour: matt aluminium
material: aluminum
version: adjustable
dimension: H=53 mm
protection type: IP44
ldt intern: 8.2021
EPREL Lichtquelle: 1032188

Druckfehler und Irrtümer vorbehalten. Zeichnungen und Bilder haben Skizzencharakter. Maße und technische Daten sind circa-Angaben. Längenangaben ohne Einheit in Millimeter. Objektfotos stellen Beispielanwendungen unabhängig von der tatsächlichen Wirkung dar.
Änderungen im Programm, in der Technik und in der Ausführung (ohne Ankündigung) vorbehalten. Farbabweichungen sind drucktechnisch bedingt und möglich.
Version: 2024-03-28 13:18:48

Adresse/Kontakt

A.L.S. Architektonische Lichtsysteme GmbH
Mastorter Str. 31 | 88069 Tettnang (Germany)
tel.: +49 7542 9344-0 | Fax: +49 7542 9344-30
E-Mail: info@als.de | Web: www.als.de