EVA-25NW1D



Light up with: LED
System power: 25 W
Luminous flux: 3228 lm
colour temperature: 4000 K
colour rendering index: CRI >80
beam angle: 90 °
Power supply: with power supply
connection voltage: AC 200-240 V
system efficiency: 129 lm/W
protection class: 1
outside diameter: 228 mm
wall and ceiling cut: 205 mm
weight: 0,808 kg
colour: white
INFO*: Dimmable with inverse or foreward phase control
ldt intern: 11.2020
lifespan: > 35.000 h
dimension: H=40 mm
protection type: IP54
EPREL Lichtquelle: 1194860

Druckfehler und Irrtümer vorbehalten. Zeichnungen und Bilder haben Skizzencharakter. Maße und technische Daten sind circa-Angaben. Längenangaben ohne Einheit in Millimeter. Objektfotos stellen Beispielanwendungen unabhängig von der tatsächlichen Wirkung dar.
Änderungen im Programm, in der Technik und in der Ausführung (ohne Ankündigung) vorbehalten. Farbabweichungen sind drucktechnisch bedingt und möglich.
Version: 2024-05-03 14:25:28

Adresse/Kontakt

A.L.S. Architektonische Lichtsysteme GmbH
Mastorter Str. 31 | 88069 Tettnang (Germany)
tel.: +49 7542 9344-0 | Fax: +49 7542 9344-30
E-Mail: info@als.de | Web: www.als.de