UDL-25NW2D



quantity lamps: 10
Light up with: LED linear light fitting
System power: 25 W
Luminous flux: 1827 lm
colour temperature: 4000 K
colour rendering index: >90
beam angle: 36 °
Power supply: incl. external power supply
connection voltage: 220-240 V
system efficiency: 73 lm/W
protection class: 2
wall and ceiling cut: L=272*W=37 mm
colour: black
material: body in coated die-cast-aluminium
version: reflectors in PMMA, not dimmable
INFO*: Quick-release springs
dimension: L=280*W=45*H=51 mm
protection type: IP20
EPREL Lichtquelle: 1194656

Druckfehler und Irrtümer vorbehalten. Zeichnungen und Bilder haben Skizzencharakter. Maße und technische Daten sind circa-Angaben. Längenangaben ohne Einheit in Millimeter. Objektfotos stellen Beispielanwendungen unabhängig von der tatsächlichen Wirkung dar.
Änderungen im Programm, in der Technik und in der Ausführung (ohne Ankündigung) vorbehalten. Farbabweichungen sind drucktechnisch bedingt und möglich.
Version: 2024-05-03 19:57:06

Adresse/Kontakt

A.L.S. Architektonische Lichtsysteme GmbH
Mastorter Str. 31 | 88069 Tettnang (Germany)
tel.: +49 7542 9344-0 | Fax: +49 7542 9344-30
E-Mail: info@als.de | Web: www.als.de