
ELEDR-40NW31P





quantity lamps: 1
Light up with: SMD LED
System power: 42 W
Luminous flux: 3863 lm
colour temperature: 4000 K
colour rendering index: CRI >80
Power supply: Built-in electronic power supply inside ceiling rosette
connection voltage: 220-240 V
system efficiency: 92 lm/W
protection class: 2
outside diameter: 600 mm
colour: white
material: frame white, anodised aluminium
version: light distribution: direct/indirect
INFO*: diffuser opal, incl. suspension kit
dimension: H=frame 20mm; H=total 1000 mm
UGR*: 19

Druckfehler und Irrtümer vorbehalten. Zeichnungen und Bilder haben Skizzencharakter. Maße und technische Daten sind circa-Angaben. Längenangaben ohne Einheit in Millimeter. Objektfotos stellen Beispielanwendungen unabhängig von der tatsächlichen Wirkung dar.
Änderungen im Programm, in der Technik und in der Ausführung (ohne Ankündigung) vorbehalten. Farbabweichungen sind drucktechnisch bedingt und möglich.
Version: 2024-03-29 10:09:47

Adresse/Kontakt

A.L.S. Architektonische Lichtsysteme GmbH
Mastorter Str. 31 | 88069 Tettnang (Germany)
tel.: +49 7542 9344-0 | Fax: +49 7542 9344-30
E-Mail: info@als.de | Web: www.als.de