
UAL-60WWNW31





Light up with: SMD LED
System power: 55 W
colour rendering index: CRI >80
beam angle: 120 °
Power supply: Incl. OSRAM power supply
connection voltage: AC 220-240 V
protection class: 1
outside diameter: 800 mm
colour: white
surface: Opal PMMA Diffusor
material: aluminum
version: Cable suspension included in scope of delivery for pendulum mounting, L=3000mm
INFO*: 3000K=6306lm (115 lm/W) 4000K=6589lm (120 lm/W) - switchable from 3000/4000K on the rosette inside.
lifespan: > 50.000 h
protection type: IP40
ldt intern: 6.2021
dimension: H=86 mm
EPREL Lichtquelle: 1195815
EPREL Lichtquelle 2: 1195820

Druckfehler und Irrtümer vorbehalten. Zeichnungen und Bilder haben Skizzencharakter. Maße und technische Daten sind circa-Angaben. Längenangaben ohne Einheit in Millimeter. Objektfotos stellen Beispielanwendungen unabhängig von der tatsächlichen Wirkung dar.
Änderungen im Programm, in der Technik und in der Ausführung (ohne Ankündigung) vorbehalten. Farbabweichungen sind drucktechnisch bedingt und möglich.
Version: 2024-03-28 10:16:58

Adresse/Kontakt

A.L.S. Architektonische Lichtsysteme GmbH
Mastorter Str. 31 | 88069 Tettnang (Germany)
tel.: +49 7542 9344-0 | Fax: +49 7542 9344-30
E-Mail: info@als.de | Web: www.als.de