
BWS-40NW17-7S





quantity lamps: 1
Light up with: CoB-LED
System power: 39 W
Luminous flux: 5182 lm
colour temperature: 4000 K
colour rendering index: CRI >90
beam angle: 15 °
pivotable: 130 °
Power supply: with power supply
connection voltage: 220-240 V
operating current: 1050 mA
system efficiency: 133 lm/W
protection class: 1
outside diameter: 99 mm
weight: 1,600 kg
colour: light grey
material: body in coated die-cast-aluminium, clear glass
INFO*: with electronic 3-phase adapter
EPREL Lichtquelle: 989515

Druckfehler und Irrtümer vorbehalten. Zeichnungen und Bilder haben Skizzencharakter. Maße und technische Daten sind circa-Angaben. Längenangaben ohne Einheit in Millimeter. Objektfotos stellen Beispielanwendungen unabhängig von der tatsächlichen Wirkung dar.
Änderungen im Programm, in der Technik und in der Ausführung (ohne Ankündigung) vorbehalten. Farbabweichungen sind drucktechnisch bedingt und möglich.
Version: 2024-03-28 10:24:07

Adresse/Kontakt

A.L.S. Architektonische Lichtsysteme GmbH
Mastorter Str. 31 | 88069 Tettnang (Germany)
tel.: +49 7542 9344-0 | Fax: +49 7542 9344-30
E-Mail: info@als.de | Web: www.als.de