SLC-30NW12S



quantity lamps: 1
Light up with: CoB-LED
System power: 26 W
Luminous flux: 2350 lm
colour temperature: 4000 K
colour rendering index: CRI >90
beam angle: 15 °
pivotable: 90 °
Power supply: with power supply
connection voltage: 220-240 V
system efficiency: 90 lm/W
protection class: 2
outside diameter: 84 mm
colour: black
material: body in coated die-cast-aluminium, clear glass
version: EUTRAC®-3-phase-adapter
INFO*: dimmable version, DALI or surface mounted with ceiling rose on request
protection type: IP20
EPREL Lichtquelle: 989285

Druckfehler und Irrtümer vorbehalten. Zeichnungen und Bilder haben Skizzencharakter. Maße und technische Daten sind circa-Angaben. Längenangaben ohne Einheit in Millimeter. Objektfotos stellen Beispielanwendungen unabhängig von der tatsächlichen Wirkung dar.
Änderungen im Programm, in der Technik und in der Ausführung (ohne Ankündigung) vorbehalten. Farbabweichungen sind drucktechnisch bedingt und möglich.
Version: 2024-04-20 10:32:53

Adresse/Kontakt

A.L.S. Architektonische Lichtsysteme GmbH
Mastorter Str. 31 | 88069 Tettnang (Germany)
tel.: +49 7542 9344-0 | Fax: +49 7542 9344-30
E-Mail: info@als.de | Web: www.als.de