BLE-12WWSCW1S



quantity lamps: 1
Light up with: SMD LED
System power: 12 W
Luminous flux: 1320 lm
colour rendering index: CRI >80
beam angle: 120 °
Power supply: with power supply
connection voltage: AC 230 V
system efficiency: 110 lm/W
protection class: 2
mechanical load: IK10
colour: white
material: PMMA
version: motion sensor
INFO*: 3000K=1255lm (105 lm/W) 4000K=1294lm (108 lm/W), 6000K=1320lm (110 lm/W) - switchable between 3000/4000/6000K
lifespan: 45.000 h
protection type: IP54
dimension: L=220*W=220*H=48 mm
UGR*: 24,45
ldt intern: 8.2021
EPREL Lichtquelle: 1172873

Druckfehler und Irrtümer vorbehalten. Zeichnungen und Bilder haben Skizzencharakter. Maße und technische Daten sind circa-Angaben. Längenangaben ohne Einheit in Millimeter. Objektfotos stellen Beispielanwendungen unabhängig von der tatsächlichen Wirkung dar.
Änderungen im Programm, in der Technik und in der Ausführung (ohne Ankündigung) vorbehalten. Farbabweichungen sind drucktechnisch bedingt und möglich.
Version: 2024-05-06 01:49:52

Adresse/Kontakt

A.L.S. Architektonische Lichtsysteme GmbH
Mastorter Str. 31 | 88069 Tettnang (Germany)
tel.: +49 7542 9344-0 | Fax: +49 7542 9344-30
E-Mail: info@als.de | Web: www.als.de