BLR-12WWSCW1S



quantity lamps: 1
Light up with: SMD LED
System power: 12 W
Luminous flux: 1364 lm
colour rendering index: CRI >80
beam angle: 120 °
Power supply: with power supply
connection voltage: AC 230 V
system efficiency: 114 lm/W
protection class: 2
mechanical load: IK10
outside diameter: 220 mm
colour: white
material: PMMA
version: motion sensor
INFO*: 3000K=1297lm (108 lm/W) 4000K=1337lm (111 lm/W), 6000K=1364lm (114 lm/W) - switchable between 3000K/4000K/6000K
protection type: IP54
dimension: H=48 mm
ldt intern: 8.2021
UGR*: 24,4
lifespan: 45.000 h

Druckfehler und Irrtümer vorbehalten. Zeichnungen und Bilder haben Skizzencharakter. Maße und technische Daten sind circa-Angaben. Längenangaben ohne Einheit in Millimeter. Objektfotos stellen Beispielanwendungen unabhängig von der tatsächlichen Wirkung dar.
Änderungen im Programm, in der Technik und in der Ausführung (ohne Ankündigung) vorbehalten. Farbabweichungen sind drucktechnisch bedingt und möglich.
Version: 2024-05-03 13:13:00

Adresse/Kontakt

A.L.S. Architektonische Lichtsysteme GmbH
Mastorter Str. 31 | 88069 Tettnang (Germany)
tel.: +49 7542 9344-0 | Fax: +49 7542 9344-30
E-Mail: info@als.de | Web: www.als.de