PASUP70A-3NW



quantity lamps: 1
Light up with: LED
System power: 3 W
Luminous flux: 105 lm
colour temperature: 4000 K
colour rendering index: CRI >80
beam angle: 38 °
Power supply: with external driver
connection voltage: DC 24 V
system efficiency: 35 lm/W
protection class: 1
mechanical load: IK08
passable by persons: 1000 kg
material: housing: primary aluminium
version: glass transparent 6 mm, square cover stainless steel
INFO*: incl. light body, cover, external driver, installation box
lifespan: L80 B20; 60.000 h
protection type: IP67
ldt intern: 7.2021
EPREL Lichtquelle: 982851

Druckfehler und Irrtümer vorbehalten. Zeichnungen und Bilder haben Skizzencharakter. Maße und technische Daten sind circa-Angaben. Längenangaben ohne Einheit in Millimeter. Objektfotos stellen Beispielanwendungen unabhängig von der tatsächlichen Wirkung dar.
Änderungen im Programm, in der Technik und in der Ausführung (ohne Ankündigung) vorbehalten. Farbabweichungen sind drucktechnisch bedingt und möglich.
Version: 2024-04-28 01:19:30

Adresse/Kontakt

A.L.S. Architektonische Lichtsysteme GmbH
Mastorter Str. 31 | 88069 Tettnang (Germany)
tel.: +49 7542 9344-0 | Fax: +49 7542 9344-30
E-Mail: info@als.de | Web: www.als.de