QUANA3HR-4NW6

quantity lamps: 1
Light up with: LED
System power: 4,5 W
Luminous flux: 47 lm
colour temperature: 4000 K
colour rendering index: CRI >80
Power supply: with built-in driver
connection voltage: 220-240 V
system efficiency: 10 lm/W
protection class: 2
test certificates: ENEC
mechanical load: IK10
wall and ceiling cut: 201x84 mm
installation depth: 58 mm
colour: anthracite
material: aluminum
version: symmetric
INFO*: incl. Mask, installation box, light body and power supply
dimension: L=190*W=67*H=74 mm
lifespan: L80 B20; 60.000 h
protection type: IP65
ldt intern: 6.2021

Druckfehler und Irrtümer vorbehalten. Zeichnungen und Bilder haben Skizzencharakter. Maße und technische Daten sind circa-Angaben. Längenangaben ohne Einheit in Millimeter. Objektfotos stellen Beispielanwendungen unabhängig von der tatsächlichen Wirkung dar.
Änderungen im Programm, in der Technik und in der Ausführung (ohne Ankündigung) vorbehalten. Farbabweichungen sind drucktechnisch bedingt und möglich.
Version: 2024-05-06 00:06:18

Adresse/Kontakt

A.L.S. Architektonische Lichtsysteme GmbH
Mastorter Str. 31 | 88069 Tettnang (Germany)
tel.: +49 7542 9344-0 | Fax: +49 7542 9344-30
E-Mail: info@als.de | Web: www.als.de