
DXS-54NW08





Light up with: POWER LED
System power: 6 W
Luminous flux: 149 lm
colour temperature: 4000 K
colour rendering index: CRI >80
beam angle: 52 °
pivotable: 220 °
Power supply: with power supply
connection voltage: 220-240V 50/60Hz V
system efficiency: 25 lm/W
protection class: 2
outside diameter: 54 mm
colour: bronze
material: housing: alu eloxiert
INFO*: Installation height: 70mm, spit height: 250mm
ldt intern: 5.2021
dimension: L=105*H=90 mm
protection type: IP65

Druckfehler und Irrtümer vorbehalten. Zeichnungen und Bilder haben Skizzencharakter. Maße und technische Daten sind circa-Angaben. Längenangaben ohne Einheit in Millimeter. Objektfotos stellen Beispielanwendungen unabhängig von der tatsächlichen Wirkung dar.
Änderungen im Programm, in der Technik und in der Ausführung (ohne Ankündigung) vorbehalten. Farbabweichungen sind drucktechnisch bedingt und möglich.
Version: 2024-03-29 13:01:43

Adresse/Kontakt

A.L.S. Architektonische Lichtsysteme GmbH
Mastorter Str. 31 | 88069 Tettnang (Germany)
tel.: +49 7542 9344-0 | Fax: +49 7542 9344-30
E-Mail: info@als.de | Web: www.als.de