LUN-25WW7



Light up with: LED
System power: 27 W
Luminous flux: 2454 lm
colour temperature: 3000 K
colour rendering index: CRI >80
Power supply: with power supply
connection voltage: 50/60Hz, 230 V
system efficiency: 91 lm/W
protection class: 1
mechanical load: IK10
outside diameter: 365 mm
colour: light grey
material: die-cast aluminum
version: emergency version 3h
INFO*: In emergency light mode 130lm
dimension: H=70 mm
lifespan: L70 B20; 50.000 h
protection type: IP65
EPREL Lichtquelle: 844548

Druckfehler und Irrtümer vorbehalten. Zeichnungen und Bilder haben Skizzencharakter. Maße und technische Daten sind circa-Angaben. Längenangaben ohne Einheit in Millimeter. Objektfotos stellen Beispielanwendungen unabhängig von der tatsächlichen Wirkung dar.
Änderungen im Programm, in der Technik und in der Ausführung (ohne Ankündigung) vorbehalten. Farbabweichungen sind drucktechnisch bedingt und möglich.
Version: 2024-05-06 21:42:08

Adresse/Kontakt

A.L.S. Architektonische Lichtsysteme GmbH
Mastorter Str. 31 | 88069 Tettnang (Germany)
tel.: +49 7542 9344-0 | Fax: +49 7542 9344-30
E-Mail: info@als.de | Web: www.als.de