TRN-34NW7F



Light up with: LED
System power: 34,5 W
Luminous flux: 1684 lm
colour temperature: 4000 K
colour rendering index: CRI >80
beam angle: 90 °
Power supply: with built-in driver
connection voltage: 230 V
operating current: 350 mA
system efficiency: 49 lm/W
protection class: 2
mechanical load: IK08
weight: 4,534 kg
colour: light grey
material: die-cast aluminum
version: emergency version 3h
lifespan: L80 B20; 60.000 h
dimension: L=281*W=242*H=242 mm
protection type: IP65
ldt intern: 7.2021

Druckfehler und Irrtümer vorbehalten. Zeichnungen und Bilder haben Skizzencharakter. Maße und technische Daten sind circa-Angaben. Längenangaben ohne Einheit in Millimeter. Objektfotos stellen Beispielanwendungen unabhängig von der tatsächlichen Wirkung dar.
Änderungen im Programm, in der Technik und in der Ausführung (ohne Ankündigung) vorbehalten. Farbabweichungen sind drucktechnisch bedingt und möglich.
Version: 2024-03-29 00:49:16

Adresse/Kontakt

A.L.S. Architektonische Lichtsysteme GmbH
Mastorter Str. 31 | 88069 Tettnang (Germany)
tel.: +49 7542 9344-0 | Fax: +49 7542 9344-30
E-Mail: info@als.de | Web: www.als.de