K3-2NW1B



quantity lamps: 2
Light up with: LED
System power: 8 W
Luminous flux: 248 lm
colour temperature: 4000 K
colour rendering index: 80
lifespan: L80 B20; 60.000 h
beam angle: 2x70 °
Power supply: with built-in driver
connection voltage: 230 V
operating current: 700 mA
system efficiency: 31 lm/W
protection type: IP65
protection class: 2
mechanical load: IK08
dimension: L=100*W=102*H=100 mm
colour: white
surface: UV-stabilized paint
material: die-cast aluminum
version: 2 emissions
EPREL Lichtquelle: 982851

Druckfehler und Irrtümer vorbehalten. Zeichnungen und Bilder haben Skizzencharakter. Maße und technische Daten sind circa-Angaben. Längenangaben ohne Einheit in Millimeter. Objektfotos stellen Beispielanwendungen unabhängig von der tatsächlichen Wirkung dar.
Änderungen im Programm, in der Technik und in der Ausführung (ohne Ankündigung) vorbehalten. Farbabweichungen sind drucktechnisch bedingt und möglich.
Version: 2024-05-05 11:41:28

Adresse/Kontakt

A.L.S. Architektonische Lichtsysteme GmbH
Mastorter Str. 31 | 88069 Tettnang (Germany)
tel.: +49 7542 9344-0 | Fax: +49 7542 9344-30
E-Mail: info@als.de | Web: www.als.de